

# QUICK COUPLING serie 021



**Interchangeability:** Rectus 21    **Max. Pressure:** 35 Bar

**Material:** Standard

**Coupling:** Brass    **Temp. range:** -20 °C - +100 °C

**Sleeve:** Brass    **Flow:** 600 l/min

**Valve:** Brass


**Plug:** Brass

**Seals:** NBR

Also available in Nickel Plated and Stainless Steel - AISI 316




**Coupling**  
Hose Barb




211004	4mm
211006	6mm
211008	8mm
211009	9mm
211010	10mm

**Coupling**  
Parallel Male Threads




211110	1/8"
211113	1/4"
211117	3/8"
2111M12	M12x1,5
2111M14	M14x1,5

**Coupling**  
Female Threads




211210	1/8"
211213	1/4"
211217	3/8"
211812	M12x1,5
211814	M14x1,5

**Plug**  
Hose Barb




215004	4mm
215005	5mm
215006	6mm
215008	8mm
215009	9mm
215010	10mm

**Plug**  
Parallel Male Threads



215110	1/8"
215113	1/4"
215117	3/8"
2151M10	M10x1
2151M12	M12x1,5
2151M14	M14x1,5

**Plug**  
Female Threads



215210	1/8"
215213	1/4"
215217	3/8"
2152M10	M10x1
2152M12	M12x1,5
2152M14	M14x1,5