



K-MAX 55 – 10

Stationär ljuddämpad skruvkompressor.

- + Direktdrivet skruvblock, effektivt och driftsäkert
- + Kompakt design, lätt placerad och enkel installation
- + Kontrollbox EasyTronic IV med LCD display, möjlighet att ansluta upptill 4 enheter
- + Termostatstyrd centrifugal fläkt, effektiv och tyst kylning
- + Förfilter-panel, ren och dammfri insida för ökad brukstid
- + Spin-On filter för enkel och effektivt underhåll

Art.nr.	Benämning	Volt	kW	l/min	Bar	dBA	Vikt kg	Dim lxbxh cm
100 103 389	K-MAX 55-10	400/3	55	8.300	10	72	1251	173x127x170

TECHNICAL FEATURES

Technical characteristics*	Type	55
Working pressure	bar g	10
Air-end	type	FS260
Max F.a.d (according to ISO 1217)	l/min	8300
Oil quantity	l	26
Oil quantity for topping-up	l	1,5
Max air temperature above ambient	°C	10
Re-claimable heat	kJ/h	188000
Cooling fan rate	m3/h	6000
Oil carry over	mg/m3	2-4
Electric motor	type	
Rated power	kW	55
Max. power absorbed, ventilation included	kW	61,9
Electrical box protection class	IP	54
Maximum ambient temperature	°C	+2/+45
Noise level (according Pneurop/Cagi PN2CPTC2)	dB(A)	72
Electrical data		
Voltage	V/Ph/Hz	400/3 ~/50
Auxiliary voltage	V/Ph/Hz	24/1~/50
Start-up absorbed current	A	
Max. absorbed current, ventilation included	A	105
Idle running absorbed power	kW	15,5
Electrical motor protection class	IP	55
Motor insulation class		F
Service factor		1,1
Protection devices		
Max oil temperature	°C	110
Pre-alarm oil temperature	°C	105
Motor overload switch setting	A	PTC
Safety valve setting	bar	14
Dimensions		
Length	mm	1730
Width	mm	1270
Height	mm	1700
Weight	kg	1251
Air outlet size	G	2"

